

INTRODUCTION

The **BRF14** high-temperature furnace features a chamber capacity that varies from 5 to 27 liters in its standard configurations. Additional chamber sizes and volumes are available in customized models.

The **BRF14/10** high-temperature furnace has a capacity of 10 liters.

SPECIFICATIONS

Maximum Temperature: 1400°C

Maximum Continuous Temperature: 1350°C

Chamber dimensions (mm): 190 x 180 x 310 (H x W x D)

Silicon carbide rod heating elements offer an extended operational lifespan and withstand the stress of intermittent operation

Energy efficient, high quality, low thermal mass ceramic fiber insulation

A manually operated, insulated vertical lift door opens upward and outward, keeping the hot face away from the operator

To ensure maximum operator safety, a positive break door switch isolates power from the heating elements whenever the door is opened

High end Microprocessor PID controller

R type Thermocouple

A small ceramic chimney is fitted as standard



BRF14/10

External Dimensions (mm): 780 x 635 x 715 (H x W x D)
(Indicative)

Net Wt.: 74 kg

Supply / Power: 230V– 1 Phase – 7.5 kW (Nominal)
10.5 kW (Peak power)

OPTIONS

Electrically operated door

Multi segment, multi program storage Controller

Digital over-temperature protection

Elite Thermal Systems Ltd

Elite Court, 6 Stuart Road, Market Harborough, Leicestershire LE16 9PQ, UK

Tel: +44 (0)1858 469834 | E-mail: contact@elitefurnaces.com | Website: www.elitefurnaces.com