

Data Sheet

Model: TLCF12/125

Top Loading Chamber Furnaces



INTRODUCTION

TLCF12 Top Loading Chamber Furnaces are suited to application which involve heavy loads, where samples are contained in tall crucibles, or where there is a danger of spillage onto the base of the chamber and is available in various capacities ranging from 5 litres to 125 litres in standard versions. Other chamber capacities/volumes are offered in custom-built models.

The **TLCF12/125** chamber furnace has a 125-liter capacity.

SPECIFICATIONS

Maximum Temperature: 1200°C

Maximum Continuous Temperature: 1150°C



TLCF12/125

| Floor mounted design

| Chamber dimensions (mm): 620 x 450 x 450 (H x W x D)

| Energy efficient, high quality, low thermal mass brick insulation

| These heating elements are robust cast refractory panels mounted on all sides

| Type 'R' thermocouple

| A lever allows the operator to open and close top opening door safely and conveniently

| High end Microprocessor PID controller

| Exhaust port to assist fumes removal is fitted to the furnace door

| **External Dimensions (mm):** 1175 x 950 x 950 (H x W x D)
(Indicative)

[Dimensions with door closed]

| Supply / Power: 400V– 3 Phase – 18.0 kW

OPTIONS

| Independent Over-temperature protection system

| Multi segment, multi program storage controllers

| Monitoring probes

Elite Thermal Systems Ltd

Elite Court, 6 Stuart Road, Market Harborough, Leicestershire LE16 9PQ, UK

Tel: +44 (0)1858 469834 | E-mail: contact@elitefurnaces.com | Website: www.elitefurnaces.com