

AF2000 MultiFlow Series

Mid Temperature AF4



Universal Particle/Polymer/Protein Separator

AF2000 MultiFlow Series

Asymmetric Flow Field-Flow Fractionation, also called AF4, is an innovative new separation method for the efficient separation and characterization of proteins, polymers and nanoparticles in a fast and gentle way. The AF2000 MT from Postnova is the most advanced AF4 system on the market today and is the benchmark for the industry, indicating the maximum possible performance. The instrument shows a higher resolving power and a more advanced software system than every other device available. It is the most integrated system and the only one with the channel inside the housing. The system has a large, nearly universal separation range. Nanoparticles can be separated from 1 nm to 100 µm and proteins, peptides, polymers from 10E3 to 10E12 Da. The fast & gentle separation occurs based on the diffusion coefficient in an open flow channel without using ANY stationary phase as is utilized in the technology of SEC/GPC.

UNIQUE FEATURES OF AF2000 MT

Patented Channel Cartridge Design

The AF2000 MT, as all other Postnova AF4 systems as well, is equipped with a special patented flow channel using a channel cartridge and a channel holder for fast and easy exchange of membrane and system cleaning procedure. Depending on the application, the cartridge can be replaced by different other cartridges, which are available, analog to different HPLC columns in a chromatography system.

Complete Bio-Compatible System

The AF2000 MT is the only system which can be delivered as a completely inert bio-compatible and metal-free system with a ceramic frit instead of a stainless steel frit, PEEK pumps, PEEK/PMMA channel and PEEK autosampler.

Totally Integrated One-Box-System

Completely integrated system with all important parts located inside the system housing, including flow channel. Professional one-box system for use in laboratories with high-level expectations concerning system handling and user-friendliness.

Patented Cross-Flow Control

Special patented cross-flow control, using a unique dual syringe pump module with non-pulsing cross-flow delivery for most precise separation conditions. Completely inert, metal-free cross flow path made of glass, PEEK and Teflon/PVDF. Instant cross-flow adjustment without time-delay or hysteresis (flow over and under adjustments) known from other commonly used cross-flow control valves. Rugged cross-flow control insensitive to plugging without the need for fragile and corrosion sensitive valve needles. Cross flow range from 5 µL/min (with 100 µL syringe) up to 16 mL/min (with 2 mL syringe) for lowest and highest possible cross-flows of all FFF systems. Different syringes available, which can be exchanged to extend flow rate range.

Data Evaluation Software - NovaFFF Analysis

Postnova offers a special data evaluation software with unique features. Data files from different Postnova FFF system/techniques can be processed. Software allows to perform absolute size calculation based on FFF theory and size calculation based on calibration with particle size standards. Possibility to calculate size of small particles by using a concentration detector (UV / RI) when light scattering is poor/not showing a sufficient signal. NovaFFF Analysis is an additional validation tool providing particle sizes of aggregates which can be directly compared with particles sizes from light scattering.

Integrated Method Wizard Expert System

Postnova offers a special NovaFFF control software with integrated Expert System. Method Wizard for accelerated and automated method generation by simply entering in the approximate size of the analyte. Advanced Simulation Module which is also directly integrated in the control software and where the user can run a complete method in a simulation first. Run Parameter Optimization Tool to optimize run conditions in terms of run time, maximum resolution, etc ...

Patented FOCUS Technology

The AF2000 MT uses Postnova's patented FOCUS technology which assures constant and continuous flow through the detectors all the time. That's why the system has a higher recovery, higher resolution and greater flexibility than other systems. Now AF4 can be coupled to flow sensitive viscometers and RI detectors successfully.

APPLICATIONS OF AF2000 MT

Biotechnology : Viruses, Aggregates, Cell Organelles, Bioparticles
Pharma : Proteins, Antibodies, Liposomes, Drug Delivery, Micelles
Environment : Humic and Fulvic Acid, Environmental Colloids, Clay Particles
Material Science : Latex Beads, Nanoparticle, High-Tech Nano Materials
Polymers : Biopolymers, Starches, Polyelectrolytes, Technical Polymers

Technical specifications are subject to change without further notice.

Specifications

- Principle Measurement Range:
Particles : 1 nm to 100 µm
Polymers : 500 Da to 10E12 Da
- Temperature Range:
5°C cooling up to 80°C heating
- Channel Dimensions:
Volume : between 0.5 - 2.5 mL
Size : 335 x 60 x 40 mm
Thickness : 250 µm (other sizes available on request)
- Carrier Liquids:
Aqueous : any aqueous liquid,
pH from 2 - 11, ionic strength from d.i. water to saline
Organic : THF, MeOH, etc.
- Membranes:
reg. cellulose, PC, PES
Molar Mass : 0.3; 1; 2; 4; 5; 10; 30; 100 kDa
- Detectors:
UV, RI, laser light scattering, viscosimetry, fluorescence and more; multiple detectors in line
- Channel Flow Range:
0 - 10 mL/min
- Cross Flow Range:
0 - 8.5 mL/min
- Pressure Limit:
0 - 35 bar
- Power Requirements:
110V or 240V, 50/60 Hz; 2.5 A
- PC Requirements:
Windows, min. 64 MB RAM, 2 RS232 ports
- System Software:
NovaFFF AF2000 Control
NovaFFF Analysis
- Maintenance Parts:
Consumables: pistons and piston seals, inline filters, membranes
- Injection volume:
1 - 1000 µL
Standard 20 µL
optional > 1000 µL
- Injected sample mass:
Typical injection mass 20 - 100 µg
- Injection method:
Via manual injection valve or via PN5300 autosampler

Contact

- Postnova Analytics GmbH
86899 Landsberg, GERMANY
T: +49 8191 985 688 0
- Postnova Analytics UK Ltd.
Herefordshire, WR6 5BT, UK
T: +44 1885 475007
- Postnova Analytics Inc.
84102 Salt Lake City, USA
T: +1 801 521 2004
- Postnova North Europe
01630 Vantaa, FINLAND
T: +358 9 8545 510

info@postnova.com
www.postnova.com