



POSTnova
Leading in FFF

PN3211 UVD

2-Channel UV Detector



PN3211 UV Detector

Features

The PN3211 2-channel UV Detector provides an exceptional level of sensitivity and stability. As a high sensitive UV detector, the PN3211 has a noise level of 0.5×10^{-5} AU max., making it to one of most sensitive UV detectors (ASTM Standards).

- **Greater Baseline Stability**

Supplied as standard, a temperature-controlled flow cell eliminates inconsistencies caused by changes in absorbance due to shifts in room temperature. This helps increase the baseline stability and the analysis reliability.

- **Superior Linearity ≥ 2 AU**

Using newly developed signal processing technology, the stray-light correction function has been enhanced, and the linearity has been improved. This expanded linearity combines various noise-reduction technologies to provide users with a wide dynamic range and allows the analysis of your target compound and minor impurities in a single run.

- **Internal Validation Protocol**

The incorporation of a low-pressure mercury lamp for wavelength calibration ensures simple calibration in the ultraviolet region.

- **Dual-Wavelength Measurement**

Monitor two components in the UV range simultaneously.

Ordering Information

S-DET-3211-001 PN3211 UV Detector

Flow Cells

Z-DET-3211-001	Analytical, Peek
Z-DET-3211-002	Analytical, Stainless Steel
Z-DET-3211-003	Preparative, Stainless Steel

Detector Lamps

Z-DL-PN3211	D2-Lamp, Pre-aligned, Longlife
-------------	--------------------------------

Specifications

- Light Source: Deuterium lamp
- Wavelength Range: 190 – 700 nm
- Wavelength Accuracy: ± 1 nm
- Noise Level: $\pm 0.25 \times 10^{-5}$ AU max.
- Drift:
 - 1 $\times 10^{-4}$ AU/h max. (250 nm, room temperature constant, air in cell)
 - 3 $\times 10^{-4}$ AU/h max. (250 nm, room temperature fluctuation less than 2°C, air in cell)
- Operating Temperature: 4 - 35°C
- Cell Temperature Range: 5°C above room temperature to 50°C, at 1°C steps
- Response:
 - 11 steps selectable (corresponding to time constant 0.02, 0.05, 0.1, 0.5, 1.0, 1.5, 2.0, 3.0, 6.0, 8.0, 10.0 sec)
- Range: 0.0001 – 2.56 AUFS (selectable in 0.0001 AUFS steps)
- Zero Adjustment: Auto zero function baseline shift function
- Wavelength Steps:
 - 1–5 nm, selectable in 5 steps
 - 2–5 nm when W lamp is used
- Scanning Speed: 10 – 50 nm/sec, in 5 steps
- Spectrum Plot: output speed 1, 3, 10 nm/sec
- Optical Path Length: 10 mm
- Cell Volume: 12 μ L
- Pressure Resistance: 12 MPa
- Wetted Surface Materials: SUS316L, quartz, PFA
- Dimensions (WxHxD): 260 x 140 x 420 mm
- Weight: 13 Kg
- Power Requirements: 100/120/220-240 V, 50/60Hz

Contact

- Postnova Analytics GmbH
86899 Landsberg, GERMANY
T: +49 8191 985 688 0
- Postnova Analytics UK Ltd.
Herefordshire, WR6 5BT, UK
T: +44 1885 475007
- Postnova Analytics Inc.
84102 Salt Lake City, USA
T: +1 801 521 2004
- Postnova North Europe
01630 Vantaa, FINLAND
T: +358 9 8545 510

info@postnova.com
www.postnova.com